

THE BEST SOLUTIONS

CX80

Multi-functional products for home, company, and garage use

SAFETY • INNOVATIVENESS • ECOLOGY



CX80 Multi-Purpose Lubricant

This specially formulated multi-purpose lubricant is made from the highest quality raw materials.

- Loosens rusted parts quickly
- Cleans and protects equipment from corrosion
- Eliminates squeaking and creaking of hinges, locks, curtain rods and other mechanical devices
- Improves the function of ignition systems, which are endangered with flooding or humid places
- Filters through moisture and forms a protective barrier between the water and the metal
- Eliminates moisture-triggered short circuits
- Suitable for electronic ignitions
- Protects vehicle locks from moisture and freezing
- Defrosts locks
- Removes dirt, dust, coloured crayons, felt tip pens, chewing gum and adhesives
- 1001 applications in industry, workshops or in the house

DESCRIPTION	SIZE	PART NUMBER
CX80 Multi-purpose lubricant	500ml x 24	CX80MP



CX80 Multi-Purpose Lubricant with Teflon®

An excellent multi-purpose product with exceptional quality of lubrication which can be used in many different industries and in the area of everyday life.

- The result after using is a coat which improves the resistance to abrasion and increases the working life
- The low-friction coefficient characteristic of TEFLON®, leading to high efficiency for electrical connections, structural fittings, military equipment, and in many other areas in which a repetitive movement of the surface is important
- Plays a major role in the bicycle industry, ideally suited for the lubrication of chains, gears, brake lines, gears, increases their working life and reduces friction between the elements and their wear and tear
- Also suitable as anti-adhesive agent
- Can be used in the process for formation of rubber and plastic components, it does not affect the stability and it makes it easier to release from the mould parts

DESCRIPTION	SIZE	PART NUMBER
CX80 Multi-purpose lubricant with Teflon®	500ml x 24	CX80TMP



CX80 Silicone Spray

For Plastics and Rubber. Colourless lubricant with high viscosity.

- Creates a protective film with excellent resistance
- Coverage of the friction surfaces with a thin layer of silicone grease leads to an effective reduction of friction and provides a long-lasting protection of the equipment
- Suitable for use at contact surfaces of plastic, metal, ceramics, rubber, etc.
- Does not stain does not adhere to dust • Non-adhesive, facilitates the removal of forms
- Operating temperatures from -60°C up to +230°C

Application:

- All kinds of sanitary equipment – conventional and lever valves (gas), seals, connectors, fittings, valves, joints
- Clean lubrication of equipment in textile, paper, and food industry
- Electric and power distribution equipment (assurance of electrical circuits)
- Energetic cases which work under extreme temperatures (from -60°C up to +230°C)
- In the automotive industry for the lubrication of links, locks, hinges, screws and sleeves

DESCRIPTION	SIZE	PART NUMBER
CX80 Silicone spray	500ml x 12	CX80SG



CX80 White Grease

Penetrates gaps, forms a lubricating layer that remains where the grease was applied.

- Non-hardening
- Non-dripping
- Non-staining
- Water and heat resistant
- Fights rust and corrosion
- Does not cause discoloration of paint
- Operating temperature from -40°C up to +100°C

Application:

- Long-lasting lubrication on auto hinges, gears, sprockets
- Locks, outdoor hinges, latches, overhead door tracks, pulleys
- Cables and guide rails

DESCRIPTION	SIZE	PART NUMBER
CX80 White grease	500ml x 12	CX80WG



CX80 Lithium Grease

Multi-purpose product for the lubrication of industrial, agricultural and motor vehicle systems. It ensures excellent lubrication under the toughest conditions.

- Resistant to water and oxidation
- Protects against attrition and corrosion
- Extends life of bearings
- Contains EP additives
- Mechanically stable and because of its soft consistency, easy to apply
- Passes the SKF EMCOR test
- Operating temperatures from -20°C up to +130°C

DESCRIPTION	SIZE	PART NUMBER
CX80 Lithium grease	500ml x 12	CX80LG



CX80 Copper Grease

Anti-Adhesive. Multi-purpose product for use under the most difficult conditions and within high temperature ranges from -30°C up to 1200°C.

- Safeguards against attrition, corrosion and high temperatures
- Ensures excellent lubrication
- Wide temperature range (-30°C to +1200°C)

Application:

- Screws and nuts
- Threads and all connected surfaces
- Fittings
- Spark plugs
- Wheel and brake discs
- Battery terminals
- Port Installations
- Revolving discs
- Highly stressed bearings of all kinds
- Elements in industrial, construction
- Other elements of industrial systems, construction, agricultural and motor vehicles

DESCRIPTION	SIZE	PART NUMBER
CX80 Copper grease	500ml x 12	CX80CG

CX80 RC43 Thread Lock - Medium Strength

Anaerobic adhesive for securing metal threaded connections with medium strength bonding. Remains liquid until isolated from oxygen in the presence of metal ions.

- Medium strength
- Resistance to vibration
- Initial binding to 15 minutes
- Increasing the force and slip for easy installation
- Temperature resistance from -55°C to +150°C
- Disassembly with manual tools
- Protection against corrosion
- Preventing leakage of thread
- Full strength after 24 hours

Application:

- Locking nuts and bolts
- Sealing
- Protects threads against loosening during vibration
- Recommended for small thread (the thread diameter up to M36)



DESCRIPTION	SIZE	PART NUMBER
CX80 RC43 Thread lock - blister pack	10ml x 20	RC4310
CX80 RC43 Thread lock	50ml x 10	RC4350

CX80 RC70 Thread Lock - High Strength

Anaerobic adhesive for securing metal threaded joints with very high bonding strength. Remains liquid until isolated from oxygen in the presence of metal ions.

- High strength
- Resistance to vibration
- Initial binding to 15 minutes
- Increasing pressure and slip for easy installation
- Resistant to temperatures from -55°C to +150°C
- Protection against corrosion
- Resistance to oiling
- Full strength after 24 hours

Application:

- Permanent locking of nuts and bolts
- Sealing
- Securing threads against loosening during vibration
- Recommended for small thread (the thread diameter up to M20)



DESCRIPTION	SIZE	PART NUMBER
CX80 RC70 Thread lock - blister pack	10ml x 20	RC7010
CX80 RC70 Thread lock	50ml x 10	RC7050

CX80 BONDICX Glue

General purpose adhesive with high viscosity and high strength.

- Fast curing
- Non-dripping
- Perfect for porous materials or when controlling adhesive flow is critical

Application:

- Metal
- Paper
- Cork
- Plastic
- Cardboard
- Foam
- Leather
- Wood



DESCRIPTION	SIZE	PART NUMBER
CX80 Bondicx gel glue - blister pack	3g x 24	RCBOND3
CX80 Bondicx glue - blister pack	5g x 24	RCBOND5



CX80 Starting Fluid

Makes starting petrol and diesel engines at low temperatures easier.

- Causes rapid engine start, extending life of the starter and the battery
- Contains an additive that lubricates upper part of the cylinder, in order to minimize the consumption of the engine failed starts
- Effective up to -50°C
- Aerosol fits all standard brackets injectors

Application:

- In passenger cars, trucks, buses, construction and agricultural machinery, boats, air planes, mining equipment

DESCRIPTION	SIZE	PART NUMBER
CX80 Starting fluid	500ml x 12	CX80SF



CX80 Brake Cleaner

Instant spray for cleaning brakes.

- Removes all sediments from asphalt, tar, dust from brake pads wear and baked-on dirt
- Eliminates brakes squeal
- Leaves no traces
- Removes brake fluid, oil and grease
- Makes rapid repair and fitting of parts easier
- Does not contain chlorinated solvents
- Degreases

Application:

- Cleans working parts of the braking system
- Can be used for cleaning carburettors and throttle (won't get into the engine or the injection system)

DESCRIPTION	SIZE	PART NUMBER
CX80 Brake cleaner	500ml x 12	CX80BC



CX80 Fan Belt Spray

Applicable for all types of drive belts. Suitable for strengthening and securing against slippages caused by heat, cold, humidity or presence of liquids

- Easy to use
- Suitable for all types of belts
- Preserves its softness, does not harden
- Protects the belt against aging
- Hinders humidity and therefore safeguards against cracks and premature wear and tear
- Increases friction, securing the belt against slippage

Application:

- For fan and flat belts, made of rubber, leather or fabric
- Particularly suitable for all types of conveyer belts in auto vehicles, lorries/trucks, busses and ship engines, agricultural equipment, in air-conditioning equipment and industry-used drive belts.

DESCRIPTION	SIZE	PART NUMBER
CX80 Fan belt spray	500ml x 12	CX80FB