



**Starter Batteries**

• Suitable for *Push Mowers, Ride-On Mowers, Quads* and *Motorcycles*



**Battery Types**

- AP: Supplied with acid back, no acid in cells before activation
- Ca/Ca: calcium / calcium technology, activated and pre-charged, no acid handling
- SLA: Sealed battery, activated and pre-charged, no acid handling,
- VRLA: Sealed, valve regulated, no water added required
- GEL: Sealed, ready to use, requires no acid handling in preparation and maintenance

TYPE	VOLTAGE	AH	LENGTH	WIDTH	HEIGHT	TERMINAL LAYOUT	POLE TYPE	JAPANESE REFERENCE	PART NUMBER
AP	12V	3	113mm	70mm	85mm	+ -	6	YTX4LBS	YTX4LBS
GEL	12V	5	113mm	70mm	85mm	+ -	6	YTX4LBS	YTX4GEL
GEL	12V	4	113mm	70mm	105mm	+ -	6	YTX5LBS	YTX5GEL
VRLA	12V	7	151mm	65mm	99mm	+ -	-	-	SBA712N
AP	12V	8	150mm	87mm	105mm	+ -	6	YTX9-BS	YTX9BS
GEL	12V	8	150mm	87mm	105mm	+ -	6	YTX9-BS	YTX9GEL
GEL	12V	10	150mm	87mm	130mm	+ -	6	YTX12-BS	YTX12GEL
AP	12V	12	134mm	80mm	160mm	+ -	1	12N12-4A-1	BA51211
AP	12V	12	150mm	87mm	145mm	+ -	6	YTX14-BS	YTX14BS
GEL	12V	12	150mm	87mm	145mm	+ -	6	YTX14-BS	YTX14GEL
GEL	12V	14	135mm	90mm	167mm	- +	6	-	BA51411GEL
GEL	12V	14	135mm	90mm	167mm	+ -	6	-	BA51412GEL
GEL	12V	18	175mm	87mm	155mm	- +	6	-	YTX20GEL
SLA	12V	18	182mm	77mm	168mm	- +	1	-	SBA1812N
AP	12V	19	176mm	101mm	156mm	- +	1	YB16L-B	BA51911
SLA	12V	20	182mm	77mm	168mm	- +	1	-	SBA2012N
AP	12V	20	205mm	90mm	162mm	- +	6	Y50-N18L-A2	BA52012
Ca/Ca	12V	24	196mm	131mm	184mm	+ -	1	U1-9	BA425298
SLA	12V	28	195mm	125mm	176mm	+ -	1	U1-9	U19SLA
SLA	12V	28	195mm	125mm	176mm	- +	1	U1R-9	U1R9SLA
SLA	12V	32	195mm	125mm	176mm	- +	1	-	SBA3212

Note: If Japanese reference you required is not listed please contact our Sales Staff for price and availability.