



Front End Loader Valve

Supplied c/w Attachment Kits.

Standard RV pressure settings: 185 bar
 Temperature range: -15° to +80°C
 Viscosity: 10/400 Cst (mm²/s)
 Recommended filtering: 18/14 ISO DIS 4406
 Hydraulic Fluid: Mineral oil

Front End Loader Valve with Floating 4th Position

TYPE	SPOOL SET-UP	PORTS					FLOW RATE	MAX WORK PRESSURE	PART NUMBER
		A1, A2, B1, B2, P2	T2	P1	T1	LS			
Open centred	1 x D/A, 1 x D/A - floating	1/2"	3/4"	1/2"	*3/4"	-	90 lpm	250 bar	CV452
Load sensing	1 x D/A, 1 x D/A - floating	1/2"	3/4"	1/2"	-	1/4"	90 lpm	250 bar	CV452LS

* T1 complete with High Pressure Carry Over (1/2" BSP).

Accessories to suit Front End Loader

ITEM	DESCRIPTION	PART NUMBER
	Attachment kit to suit WALVOIL SDM8/DL valve	AK9DSM11
	Attachment kit to suit AKON loader valve	CV452AK
	Repair kit to suit WALVOIL Joystick	AK9SC019KIT
	1.5m Joystick control cable	4K5055
	2.0m Joystick control cable	4K5060
	2.5m Joystick control cable	4K5065
	3.0m Joystick control cable	4K5070
	3.5m Joystick control cable	4K5075
	Joystick less switch	WK40010
	Joystick complete with 1 switch	WK40011
	Joystick complete with 2 switch	WK40012
	12V - 6/2 Solenoid divertor valve - 3/8" BSP	BSV38
	12V - 6/2 Solenoid divertor valve - 1/2" BSP	BSV12
	Soft drive kit 0.7 litre with manual ON / OFF valve	SDK750
	Soft drive kit 0.7 litre with electric ON / OFF valve with LED 'ON' indicator	SDK75012V
	Optional solenoid shut-off valve (N/C) for soft drive	EV2538A
	4 line Multifaster unit - 1/2" BSP	2PS06B4A
	2 line Multifaster unit - 1/2" BSP (Male section 2P206212GM and Female section 2P206212GFC)	2P206212GM 2P206212GFC
	Compact 2 line Multifaster unit - 1/2" BSP (Male section 2PB06212GMC and Female section 2PB06212GFC)	2PB06212GMC 2PB06212GFC