



**Double Acting Cylinder - Bushed (Unpainted)**

Working Pressure: 210bar  
 Material: Bore: St5.3 DIN2393 ISO H9  
 Piston: 9SMn28  
 Rod: Steel: UNI C45 SAE1045  
 Chrome: 25Mn ±5 Rating 9/120 h ISO 10289 - 1999/ISO 9227-NSS

ROD	BORE	ØD	STROKE	Z	PORTS	L	L1	CM	ØP	ØH	V	ØT	PART NUMBER
16	25	35	50	160	1/4"	33	22	31	12.1	25	25	35	DAB1625050
			100	210									DAB1625100
			150	260									DAB1625150
			200	310									DAB1625200
20	32	42	50	205	1/4"	33	35	51	16.2	30	35	40	DAB2032050
			100	255									DAB2032100
			150	305									DAB2032150
			200	355									DAB2032200
			250	405									DAB2032250
			300	455									DAB2032300
			400	555									DAB2032400
500	655	DAB2032500											
25	40	50	100	270	3/8"	40	38	65	20.25	35	40	50	DAB2540100
			150	320									DAB2540150
			200	370									DAB2540200
			250	420									DAB2540250
			300	470									DAB2540300
			400	570									DAB2540400
			500	670									DAB2540500
			600	770									DAB2540600
			700	870									DAB2540700
			800	970									DAB2540800
30	50	60	100	300	3/8"	43	42	85	25.25	40	45	60	DAB3050100
			150	350									DAB3050150
			200	400									DAB3050200
			250	450									DAB3050250
			300	500									DAB3050300
			400	600									DAB3050400
			500	700									DAB3050500
			600	800									DAB3050600
			700	900									DAB3050700
			800	1000									DAB3050800
			900	1100									DAB3050900
1000	1200	DAB30501000											
30	60	70	100	300	3/8"	50	36	83	25.25	40	45	70	DAB3060100
			150	350									DAB3060150
			200	400									DAB3060200
			250	450									DAB3060250
			300	500									DAB3060300
			350	550									DAB3060350
			400	600									DAB3060400
			450	650									DAB3060450
			500	700									DAB3060500
			600	800									DAB3060600
			700	900									DAB3060700