



Double Acting Cylinder - Bushed (Unpainted)

Working Pressure: 210bar
 Material: Bore: St52.3 DIN2393 ISO H9
 Piston: 9SMn28
 Rod: Steel: UNI C45 SAE1045
 Chrome: 25Mn ±5 Rating 9/120 h ISO 10289 - 1999/ISO 9227-NSS

ROD	BORE	ØD	STROKE	Z	PORTS	L	L1	CM	ØP	ØH	V	ØT	PART NUMBER
35	60	70	200	400	3/8"	50	36	83	25.25	40	45	70	DAB3560200
			300	500									DAB3560300
			400	600									DAB3560400
			500	700									DAB3560500
			600	800									DAB3560600
			700	900									DAB3560700
			800	1000									DAB3560800
			900	1100									DAB3560900
			1000	1200									DAB35601000
40	70	80	200	410	3/8"	50	46	82	30.25	50	55	80	DAB4070200
			250	460									DAB4070250
			300	510									DAB4070300
			350	560									DAB4070350
			400	610									DAB4070400
			450	660									DAB4070450
			500	710									DAB4070500
			600	810									DAB4070600
			700	910									DAB4070700
			800	1010									DAB4070800
900	1110	DAB4070900											
40	80	92	200	410	3/8"	60	42	70	30.25	50	55	90	DAB4080200
			250	460									DAB4080250
			300	510									DAB4080300
			350	560									DAB4080350
			400	610									DAB4080400
			500	710									DAB4080500
			600	810									DAB4080600
			700	910									DAB4080700
			800	1010									DAB4080800
			900	1110									DAB4080900
1000	1210	DAB40801000											
50	100	115	200	425	1/2"	66	45	75	30.25	60	70	115	DAB50100200
			300	525									DAB50100300
			400	600									DAB50100400600
			500	725									DAB50100500
			700	925									DAB50100700
			900	1125									DAB50100900
			1000	1225									DAB501001000