



### Hydraulic Oil H46AW

A superior grade hydraulic oil compatible with a wide range of hydraulic systems. Suitable for static industrial, mobile agricultural and earth moving machinery. Provides excellent anti-wear, anti-corrosion, anti-oxidant and anti-foam characteristics.

- Suitable for most applications.
- Superior anti-wear performance.
- Compatible with other mineral hydraulic oils.
- ISO cleanliness 15/12

| DESCRIPTION         | SIZE     | PART NUMBER |
|---------------------|----------|-------------|
| Hydraulic oil H46AW | 20 Litre | H4620       |



### Filling Cap - Type TA

Material: Galvanised steel and aluminium  
 Seals: Cork  
 Attachment: Flange  
 Filtration: 10 microns  
 Temperature: -30° to +100°C  
 Mounting: Flange mounting on tank

| DIMENSIONS |    |     | OPTIONS      | RELIEF VALVE | BASKET | PART NUMBER    |
|------------|----|-----|--------------|--------------|--------|----------------|
| A          | B  | C   |              |              |        |                |
| 52         | 29 | 111 | Without Lock | None         | C65    | TA46FL10B00C65 |
| 83         | 50 | 134 | Without Lock | None         | C80    | TA80FL10B00C80 |
| 83         | 50 | 134 | With Lock    | None         | C80    | TA80FL10B0LC80 |
| 83         | 50 | 134 | Without Lock | 0.7 bar      | C80    | TA80FL10B10C80 |