



High Pressure Quick Release Couplings

- Free Flow
- Zinc plated
- Max Pressure: 250 bar / 3600 psi

DESCRIPTION	THREAD	PART NUMBER
Female quick release coupling	3/8" BSP Female	C23543PW
Replacement seal kit to suit C23543PW	-	C23543PWSK
Male quick release coupling	3/8" BSP Female	C23544PW



Professional High Pressure Quick Release Couplings

- Free Flow
- Zinc plated
- Max Pressure: 250 bar / 3600 psi

DESCRIPTION	THREAD	PART NUMBER
Professional Female quick release coupling	3/8" BSP Female	240255PW
Professional Male quick release coupling	3/8" BSP Female	240254PW



KW Quick Release Couplings

- Zinc plated
- Max Pressure: 350 bar / 5000 psi
- Max Temperature: 150°C

DESCRIPTION	THREAD	PART NUMBER
KW Quick coupling	1/4" BSP Female	240025PW



Natural Hog Bristle Brush

DESCRIPTION	INLET	PART NUMBER
60mm Natural hog bristle brush	1/4" Female	260013PW
90mm Natural hog bristle brush	1/4" Female	260014PW



'TS200' Rotating Brush

DESCRIPTION	INLET	PART NUMBER
Horse hair bristles brush with 3mm nozzle	1/4" Male	260010PW



Foam Enhancer - Stainless Steel

Foam thickener for use with car wash brushes

DESCRIPTION	INLET	OUTLET	PART NUMBER
Foam enhancer - Ø2.5mm	1/4" Female	1/4" Male	260021PW